



iBiotec® ADERSTRAP

DATA SHEET

Last update : 09/04/2025

VEGETAL BELT DRESSING ANTI SLIP

A SLIPPING BELT WEARS OVER TIME.
A WORN BELT SLIPS EVEN MORE, SIGNIFICANTLY REDUCING MOTOR SERVICE LIFE.
A SLIPPING BELT CAN RESULT IN PRODUCTION STOPPAGES

ADERSTRAP BELT ADHESIVE can be used on ALL BELTS

flat belts, V-belts, trapezoidal belts and synchronous belts,
all materials, leathers, rubbers, polymers, polyesters, PE, PVC, PU,
polyolefins, Hytrel or silicones.

ELIMINATES

noise and squeaking and especially wear caused by slipping,
restores transmission power.

WATERPROOFING

Long-lasting protection for belts made
from materials that are sensitive to moisture.

DIRECTIONS FOR USE :

Shake the aerosol briefly before use.
Spray from a distance of 10 to 15 cm onto the belt and into the grooves,
ideally while the system is at standstill, to impregnate the entire power transmission.
Restart after 10 minutes.

PHYSICAL AND CHEMICAL PROPERTIES

| PROPERTIES | VALUES | UNITS |
|---------------------------|--------------------------|-------|
| Appearance | Liquid, cloudy, adhesive | - |
| Colour | Yellow | - |
| Density at 20°C | 0.783 ± 0,02 | kg/m3 |
| Active product | Vegetal | - |
| Internal pressure at 25°C | 2,5 | Bars |
| Internal pressure at 50°C | 5,5 | Bars |



Aerosol 650 ml

Net volume 400 ml
Item code 518215

iBiotec® Tec Industries®Service
Z.I La Massane - 13210 Saint-Rémy de Provence – France
Tél. +33(0)4 90 92 74 70 – Fax. +33 (0)4 90 92 32 32
www.ibiotec.fr

USAGE RESERVE AUX UTILISATEURS PROFESSIONNELS
Consulter la fiche de données de sécurité.

Les renseignements figurant sur ce document sont basés sur l'état actuel de nos connaissances relatives au produit concerné. Ils sont donnés de bonne foi. Les caractéristiques y figurant ne peuvent être en aucun cas considérées comme spécifications de vente. L'attention des utilisateurs est en outre attirée sur les risques éventuellement encourus lorsqu'un produit est utilisé à d'autres usages que ceux pour lequel il est conçu.

Parallèlement, le client s'engage à accepter nos conditions générales de marché de fournitures dans leur totalité, et plus particulièrement la garantie et clause limitative et exonératoire de Responsabilité. Ce document correspond à des secrets commerciaux et industriels qui sont la propriété de Tec Industries Service et, constituant un élément valorisé de son actif, ne saurait être communiqué à des tiers en vertu de la loi du 11 juillet 1979.